## 🔉 ovaga

## PAC1720-1-AIA-TR

Data Sheet

Current Sensor, Power Calculation, 525  $\mu A,$  DFN, 10 Pins, 3 V, 5.5 V

| Manufacturers | Microchip Technology, Inc |
|---------------|---------------------------|
| Package/Case  | VDFN-10                   |
| Product Type  | Power Management ICs      |
| RoHS          |                           |
| Lifecycle     |                           |



Images are for reference only

Please submit RFQ for PAC1720-1-AIA-TR or Email to us: sales@ovaga.com We will contact you in 12 hours.

<u>RFQ</u>

### **General Description**

The PAC1720 is a dual high-side bi-directional current sensing monitor with precision voltage measurement capabilities. Each sensor measures the voltage developed across an external sense resistor to represent the high-side current of a battery or voltage regulator. The PAC1720 also measures the SENSE+ pin voltage and calculates average power over the integration period. The PAC1720 can be programmed to assert the ALERT# pin when high and low limits are exceeded for Current Sense and Bus Voltage. Available in a RoHS compliant 3 X 3mm 10-pin DFN package.

The PAC1720 device is good for measuring dynamic power. The long integration time allows for extending system polling cycles without losing any power consumption information. In addition the alert ensures that transient events are captured between the polling cycles.

| Features  | Application                    |  |
|---|--------------------------------|--|
| Features  | Notebook and Desktop Computers |  |
| Dual high-side current sensor   | Industrial                     |  |
| Current measurement is integrated over 2.5ms to 2.6sec with up to 11-bit resolution     | Power Management Systems       |  |
| 1% current measurement accuracy in positive range                                       | Embedded Applications          |  |
| Measures VSOURCE voltage  |                                |  |
| Calculates proportional power   |                                |  |
| VSOURCE voltage range 0V to 40V   |                                |  |
| Bi-directional current sensing  |                                |  |
| Auto-zero input offset voltage  |                                |  |
| Digital averaging   |                                |  |
| Adjustable sampling time and resolution   |                                |  |
| 5µA typical Standby current   |                                |  |
| Programmable sense voltage range  |                                |  |
| Power supply range 3.0V to 5.5V   |                                |  |
| Wide temperature operating range: -40°C to +85°C  |                                |  |
| ALERT# output for voltage and current out of limit transients between sampling interval |                                |  |
| SMBus 2.0 communications interface  |                                |  |
| Address selectable by resistor decode   |                                |  |

Sample time configurable from 2.5ms-320ms

With averaging effective sampling times up to 2.6sec

3x3 mm DFN-10 package



### **Related Products**



PAC1710-1-AIA-TR

Microchip Technology, Inc VDFN-10



TC4421EPA Microchip Technology, Inc PDIP-8



### <u>TC4426EPA</u>

Microchip Technology, Inc PDIP-8

### **TC4426AVPA**

Microchip Technology, Inc PDIP-8

### <u>TC7662AEPA</u>

Microchip Technology, Inc PDIP-8

# TC1232EPA Microchip Tec

Microchip Technology, Inc PDIP-8

### <u>TC4424CPA</u>

Microchip Technology, Inc PDIP-8



### **TC4423EPA**

Microchip Technology, Inc PDIP-8