

Bluetooth Low Energy Module, Shielded, Antenna, ASCII Interface, 9x11.5mm

Manufacturers	Microchip Technology, Inc
Package/Case	SMD
Product Type	RF Integrated Circuits
RoHS	
Lifecycle	



Images are for reference only

Please submit RFQ for RN4871-V/RM140 or [Email to us: sales@ovaga.com](mailto:sales@ovaga.com) We will contact you in 12 hours.

[RFQ](#)

General Description

The RN4871 is a small form factor, Bluetooth Low Energy module measuring just 9 x 11.5 x 2.1 mm. This fully-integrated module is designed for easy implementation into a broad range of applications. It delivers up to 2.5x throughput improvement and more secure connections vs. Bluetooth 4.1 based products. Developers can easily interface to the device via a standard UART interface, available on most Microcontrollers and Processors. The RN4871 has a completely integrated Bluetooth software stack, and offers a shielded regulatory certified version with built-in antenna. Developers are freed from the complexities of Bluetooth Software and RF development and can simply utilize the RN4871 as a wireline replacement. Perfect for IoT (Internet of Things) applications, when interfaced to a BLE enabled smartphone or Bluetooth Internet Gateway, applications can be monitored, controlled and updated from anywhere in the world.

The Microchip Bluetooth Data (MBD) mobile app is available to speed up development for both Android and iOS.

Microchip's complimentary and confidential Wireless Check online design review service is available for customers who have selected our products for their application design-in*. *The online design review service is subject to Microchip's Program Terms and Conditions and requires a myMicrochip account.

Firmware Release Summary, see Software Release Notes for details:

RN4871-I(V)/RM140 - (FW 1.40.0) Fixes bug with random private addressing which created IOP issue with select Android devices. Added feature to turn off advertising at power-on in order to easily configure module with the host MCU before advertising. Available in industrial temperature range (I) and varying (V) for easier transition from RN4871-V/RM118.

RN4871-I/RM130- (FW 1.30.0) Fixes bug with invalid Bluetooth address. Refer to Errata document for more information.

RN4871-I/RM128- (FW 1.28.2) Introduces LE Secure Connections and Data Length Extension features among other bug fixes. Also improved the operating range to 85C.

RN4871-V/RM118- (FW 1.18.3) Initial Release.

Features

Bluetooth 5 Certified

Easy to use ASCII command interface for communication with the host microcontroller

Module certified for use in USA, Canada, Brazil, Europe, Japan, Korea, Taiwan and China

Mobile Application supported in Microchip Bluetooth Data (MBD)

Latest Firmware Revision: 1.40

Supports LE Secure Connections levels 1-3

Supports up to 151 byte payloads with Data Length Extensions

Scripting features to allow for operation without a host microcontroller

White list for determining connections

MLDP compatibility with RN4020

Remote configuration capability

Antenna: Ceramic chip Antenna or external antenna connection

Related Products



[RN52SRC-I/RM100](#)

Microchip Technology, Inc
SMD



[RN4871-V/RM130](#)

Microchip Technology, Inc
SMD



[RN4871-I/RM128](#)

Microchip Technology, Inc
SMD



[RN4871-V/RM118](#)

Microchip Technology, Inc
16-SMD SMD




[RN4871-I/RM140](#)

Microchip Technology, Inc
SMD



[RN4871-I/RM130](#)

Microchip Technology, Inc
16-SMD SMD



[RN-4870-SNSR](#)

Microchip Technology, Inc
N/A



[RN4870-I/RM140](#)

Microchip Technology, Inc
SMD