



Data Sheet

MCU 16-bit RL78 CISC 8KB Flash 2.5V/3.3V/5V 20-Pin LSSOP Tube


Manufacturers Renesas Technology Corp

Package/Case 20-LSSOP (0.173, 4.40mm Width)

Product Type Embedded Processors & Controllers

RoHS

Lifecycle



Images are for reference only

Please submit RFQ for R5F10268ASP#V5 or Email to us: sales@ovaga.com We will contact you in 12 hours.

RFQ

General Description

Features

CPU: RL78 core, Max. 24MHz

Voltage: 1.8V to 5.5V

Package: 24-pin HWQFN, 20 to 30-pin LSSOP

Memory: SRAM Max. 2KB, Program Flash Max. 16KB

Timer: 16-bit Timer (ch) x 8, 8-bit Timer (ch) x 4, Watchdog Timer (ch) x 1, 12-bit Interval Timer x 1 ch

PWM: PWM Output x 7

Analog function: 10-bit A/D Converter (ch) x 8

On-chip Oscillator Freq. (MHz): High-Speed: 1, 4, 8, 12, 16, 24MHz

Low-speed: 15kHz

Others: Power-On Reset, Low Voltage Detection



Related Products



R5F21246SNFP

Renesas Technology Corp QFP48



R5F21134FP

Renesas Technology Corp QFP-32



R5S77641N300BG

Renesas Technology Corp BGA



R5F56218BDFP#V0

Renesas Technology Corp 100-LQFP



R5F21368CNFP

Renesas Technology Corp 64-LQFP



R5S77641P300BG

Renesas Technology Corp BGA



R5F562TAADFP#V1

Renesas Technology Corp RX62T32Bit100Mhz



R5F52306ADFM#30

Renesas Technology Corp 64-LQFP