

SRAM Chip Async Single 3V/3.3V 8M-bit 512K x 16 55ns 44-Pin TSOP-II Tray

Manufacturers	Renesas Technology Corp
Package/Case	TSOP(44)
Product Type	Memory
RoHS	
Lifecycle	



Images are for reference only

Please submit RFQ for RMLV0816BGSB-4S2#AA0 or [Email to us: sales@ovaga.com](mailto:sales@ovaga.com) We will contact you in 12 hours.

[RFQ](#)

General Description

Features

Single 3V supply: 2.4V to 3.6V

Access time: Power supply voltage from 2.7V to 3.6V: 45ns (max.) Power supply voltage from 2.4V to 2.7V: 55ns (max.)

Current consumption: Standby: 0.45µA (typ.)

Equal access and cycle times

Common data input and output Three state output

Directly TTL compatible All inputs and outputs


Battery backup operation

Related Products



[RMLV0416EGSB-4S2#AA1](#)

Renesas Technology Corp
44- TSOP (0.400, 10.16mm Width)




[RMLV1616AGSD-5S2#AA1](#)

Renesas Technology Corp




[RMLV1616AGSA-5S2#AA0](#)

Renesas Technology Corp
TSOP-5



[RMLV1616AGBG-5S2#AC0](#)

Renesas Technology Corp
48-TFBGA



[RMLV0416EGSB-4S2#AA0](#)

Renesas Technology Corp



[RMLV0416EGSB-4S2#HA1](#)

Renesas Technology Corp



[RMLV0408EGSP-4S2#CA0](#)

Renesas Technology Corp
32-SOIC (0.450, 11.40mm Width)



[RMLV0408EGSB-4S2#AA1](#)

Renesas Technology Corp
TSOP-32