



Data Sheet

Operational Amplifiers - Op Amps 1.8-12V Dual Rail to

Manufacturers ON Semiconductor, LLC

Package/Case DIP-8

Product Type Op Amps

RoHS

Lifecycle



Images are for reference only

Please submit RFQ for MC33202P or Email to us: sales@ovaga.com We will contact you in 12 hours.



General Description

The MC33201/2/4 family of op-amps provides rail-to-rail operation on both the input and output. The inputs can be driven as high as 200 mV beyond the supply rails without phase reversal on the outputs, and the output can swing within 50 mV of each rail. This rail-to-rail operation enables the user to make full use of the supply voltage range available. It is designed to work at very low supply voltages (+/- 0.9 V) yet can operate with a supply of up to +12 V and ground. Output current boosting techniques provide a high output current capability while keeping the drain current of the amplifier to a minimum. Also, the combination of low noise and distortion with a high slew rate and drive capability make this an ideal amplifier for audio applications.

Features Application

Low Voltage, Single Supply Operation (+1.8 V and Ground to +12 V and Ground)

ONSEMI

Input Voltage Range Includes both Supply Rails

Output Voltage Swings within 50 mV of both Rails

No Phase Reversal on the Output for Over-driven Input Signals

High Output Current>

Low Supply Current>

600 W Output Drive Capability

Extended Operating Temperature Ranges (-40°to +105°C and -55°to +125°C)

Typical Gain Bandwidth>





Related Products



MC33204DR2G

ON Semiconductor, LLC SOIC-14



MC3403DG

ON Semiconductor, LLC SOIC-14



MC33074DR2G

ON Semiconductor, LLC SOIC-14



MC34074ADG

ON Semiconductor, LLC SOIC-14



MC33178P

ON Semiconductor, LLC DIP-8



MC33201PG

ON Semiconductor, LLC 8-PDIP



MC33204DTBR2G
ON Semiconductor, LLC
TSSOP-14



MC34074VDG

ON Semiconductor, LLC
SOIC-14