# 🔉 ovaga

## MAX803SQ293D3T1G

Data Sheet

MPU Reset Monitor, 1.2V-5.5Vsupp., 2.93V threshold/10 µs delay, Open-Drain reset, SC-70-3

Manufacturers	ON Semiconductor, LLC
Package/Case	SC-70-3
Product Type	Power Management ICs
RoHS	Rohs
Lifecycle	Images are for reference only
Please submit RFQ for MAX803SQ293D3T1G or <u>Email to us: sales@ovaga.com</u> We will contact you in 12 hours.	

## **General Description**

The MAX803/MAX809/MAX810 are microprocessor ( $\mu$ P) supervisory circuits used to monitor the power supplies in  $\mu$ P and digital systems. They provide excellent circuit reliability and low cost by eliminating external components and adjustments when used with +5V, +3.3V, +3.0V, or +2.5V powered circuits. These circuits perform a single function: they assert a reset signal whenever the VCC supply voltage declines below a preset threshold, keeping it asserted for at least 140ms after VCC has risen above the reset threshold. Reset thresholds suitable for operation with a variety of supply voltages are available. The MAX803 has an open-drain output stage, while the MAX809/MAX810 have push-pull outputs. The MAX803's open-drain active-low RESET output requires a pullup resistor that can be connected to a voltage higher than VCC. The MAX803/MAX809 have an active-low RESET output, while the MAX810 has an active-high RESET output. The reset comparator is designed to ignore fast transients on VCC, and the outputs are guaranteed to be in the correct logic state for VCC down to 1V. Low supply current makes the MAX803/MAX809/MAX810 ideal for use in portable equipment. The MAX803 is available in a 3-pin SC70 package, and the MAX809/MAX810 are available in 3-pin SC70 or SOT23 packages.

### Features

#### Precision Monitoring of +2.5V, +3V, +3.3V, and +5V Power-Supply Voltages

Fully Specified Over Temperature

- Available in Three Output Configurations
- 140ms min Power-On Reset Pulse Width
- 12µA Supply Current
- Guaranteed Reset Valid to>

Power Supply Transient Immunity

- No External Components
- 3-Pin SC70 and SOT23 Packages

AEC-Q100 Qualified. Refer to Ordering Information for Specific /V Versions

#### **Related Products**



MAX803SQ293T1G

ON Semiconductor, LLC SC-70-3

MAX803SQ308T1G

SC-70-3

D2PAK

ON Semiconductor, LLC

**NCV317MABDTRKG** 

ON Semiconductor, LLC



#### MAX803SQ463T1G

ON Semiconductor, LLC SC-70-3

LM317MABDTRKG



ON Semiconductor, LLC D2PAK

#### NCP3335ADMADJR2G

ON Semiconductor, LLC MSOP8

#### MAX809SQ293D3T1G

ON Semiconductor, LLC SC-70-3



ON Semiconductor, LLC D2PAK Application

#### ONSEMI