2) ovaga

DSPIC33EP512GM310-I/PT

Data Sheet

MCU 16-bit dsPIC 512KB Flash 3.3V 100-Pin TQFP Tray

Manufacturers	Microchip Technology, Inc
Package/Case	TQFP-100
Product Type	Embedded Processors & Controllers
RoHS	
Lifecycle	



Images are for reference only

Please submit RFQ for DSPIC33EP512GM310-I/PT or Email to us: sales@ovaga.com We will contact you in 12 hours.

General Description

Microchip's dsPIC33E family of digital signal controllers (DSCs) features a 70 MIPS dsPIC® DSC core with integrated DSP and enhanced onchip peripherals. These DSCs enable the design of high-performance, precision motor control systems that are more energy efficient, quieter in operation, have a great range and extended life. They can be used to control brushless DC, permanent magnet synchronous, AC induction and stepper motors. These devices are also ideal for high-performance general purpose applications.

Features

Operating Conditions

3.0V to 3.6V, -40°C to +85°C, up to 70 MIPS

3.0V to 3.6V, -40°C to +150°C, up to 60 MIPS

Core: 16-Bit dsPIC33E CPU

Code-Efficient (C and Assembly) Architecture

Two 40-Bit Wide Accumulators

Single-Cycle (MAC/MPY) with Dual Data Fetch

Single-Cycle Mixed-Sign MUL plus Hardware Divide

32-Bit Multiply Support

High-Speed PWM

Up to 12 PWM Outputs (six generators)	
Primary Master Time Base Inputs allow Time Base Synchronization from Internal/External Sources	
Dead Time for Rising and Falling Edges	
7.14 ns PWM Resolution	
PWM Support for DC/DC, AC/DC, Inverters, PFC, Lighting, BLDC, PMSM, ACIM, SRM	
Programmable Fault Inputs	
Flexible Trigger Configurations for ADC Conversions	
Supports PWM Lock, PWM Output Chopping and Dynamic Phase Shifting	
Advanced Analog Features	
Two Independent ADC modules	
Configurable as 10-bit, 1.1 Msps with four S&H or 12-bit, 500 ksps with one S&H	
11, 13, 18, 30 or 49 analog inputs	
Flexible and Independent ADC Trigger Sources	
Up to Four Op Amp/Comparators with Direct Connection to the ADC module	
Additional dedicated comparator	
Programmable references with 32 voltage points	
Programmable blanking and filtering	
Charge Time Measurement Unit (CTMU)	
Supports mTouch TM capacitive touch sensing	
Provides high-resolution time measurement (1 ns)	
On-chip temperature measurement	
Timers/Output Compare/Input Capture	
21 General Purpose Timers	
Nine 16-bit and up to four 32-bit timers/counters	
Eight output capture modules configurable as timers/counters	
PTG module with two configurable timers/counters	
Two 32-bit Quadrature Encoder Interface (QEI) modules configurable as a timer/counter	
Eight Input Capture modules	

Ovaga Technologies Limited

Peripheral Pin Select (PPS) to allow Function Remap

Peripheral Trigger Generator (PTG) for Scheduling Complex Sequences

Communication Interfaces

Four Enhanced Addressable UART modules (17.5 Mbps)

With support for LIN/J2602 protocols and IrDA $\ensuremath{\mathbb{R}}$

Three 3-Wire/4-Wire SPI modules (15 Mbps)

25 Mbps Data Rate for Dedicated SPI module (with no PPS)

Two I2C[™] modules (up to 1 Mbps) with SMBus Support

Programmable Cyclic Redundancy Check (CRC)

Codec Interface module (DCI) with I2S Support

Direct Memory Access (DMA)

4-Channel DMA with User-Selectable Priority Arbitration

Peripherals Supported by the DMA Controller include UART, SPI, ADC and input capture, Output compare and timers





Related Products



DSPIC30F6014A-20E/PF

TQFP-80

Microchip Technology, Inc

DSPIC30F5011-30I/PT Microchip Technology, Inc TQFP-64





DSPIC33EP512MU814-I/PH

Microchip Technology, Inc TQFP-144

DSPIC33EP512GM710-I/PF

Microchip Technology, Inc TQFP-100



DSPIC33FJ256MC710-I/PF

Microchip Technology, Inc TQFP-100



DSPIC33FJ256GP710-I/PF

Microchip Technology, Inc TQFP-100



DSPIC30F5015-30I/PT

Microchip Technology, Inc TQFP-64



DSPIC30F4011-30I/PT

Microchip Technology, Inc TQFP-44