

NSS20500UW3T2G

Data Sheet

20 V, 7.0 A, Low VCE (sat) PNP Transistor (20V, 7.0A, Low VCE (sat) PNP Transistor), Bipolar Transistors 20V PNP LOW VCE(SAT) XTR

Manufacturers	ON Semiconductor, LLC	0000
Package/Case	WDFN-3	1000
Product Type	Transistors	
RoHS	Rohs	
Lifecycle		Images are for reference only
Please submit RFO	for NSS20500UW3T2G or <u>Email to us: sales@ovaga.con</u>	<u>1</u> We will contact you in 12 hours.

General Description

Low VCE(sat) Bipolar Transistors are miniature surface mount devices featuring ultra low saturation voltage VCE(sat) and high current gain capability. These are designed for use in low voltage, high speed switching applications where affordable efficient energy control is important.

Features

Application

RFO

ONSEMI High Current, Low VCEsat, ESD Robust, High Current Gain, High Cut Off Frequency, Low Profile Package, Linear Gain (Beta)

Improved Circuit Efficiency, Decreased Battery Charge Time, Reduce component count, High Frequency Switching, Smaller Portable Product, No distortion

Related Products



NSS1C200LT1G

ON Semiconductor, LLC SOT-23-3





ON Semiconductor, LLC SC-88



NTNS3164NZT5G

ON Semiconductor, LLC XDFN3-3

NSVMUN5211DW1T3G



ON Semiconductor, LLC **SC-88**

NSVBC857BTT1G

ON Semiconductor, LLC SC-75-3

NSVUMC5NT2G



ON Semiconductor, LLC SC-88A / SC-70-5



NSVBC847BTT1G

ON Semiconductor, LLC SC-75-3



ON Semiconductor, LLC SC-88A / SC-70-5

NSVB1706DMW5T1G