



Data Sheet

Operational Amplifier, Quad, 4 Amplifier, 4 MHz, 9 V/ $\mu$ s,  $\pm$  4.5V to  $\pm$  18V, DIP, 14 Pins


Manufacturers <u>Analog Devices, Inc</u>

Package/Case DIP14

Product Type Amplifier ICs

RoHS Rohs

Lifecycle



Images are for reference only

Please submit RFQ for OP482GPZ or Email to us: sales@ovaga.com We will contact you in 12 hours.

**RFO** 

## **General Description**

The OP282/OP482 dual and quad operational amplifiers feature excellent speed at exceptionally low supply currents. Slew rate exceeds 7 V/ $\mu$ s with supply current under 250  $\mu$ A per amplifier; these unity gain stable amplifiers have a typical gain bandwidth of 4 MHz.

The JFET input stage of the OP282/OP482 insures bias current is typically a few piocamps and below 500 pA over the full temperature range. Offset voltage is under 3 mV for the dual and under 4 mV for the quad.

With a wide output swing, within 1.5 volts of each supply, low power consumption and high slew rate, the OP282/OP482 are ideal for battery-powered systems or power restricted applications. An input common-mode range that includes the positive supply makes the OP-282/OP-482 an excellent choice for high-side signal conditioning.

The OP282/OP482 are specified over the extended industrial temperature range. Both dual and quad amplifiers are available in plastic and ceramic DIPplus SOIC surface mount packages.

## **Features**

High Slew Rate: 9 V/µs

Wide Bandwidth: 4 MHz

Low Supply Current: 250 µA/Amplifier

Low Offset Voltage: 3 mV

Low Bias Current: 100 pA

Fast Settling Time

Common-Mode Range Includes V+

Unity Gain Stable

## **Related Products**



**OP213F** 

Analog Devices, Inc SMD/DIP-8/SOP-8



OP27GP

Analog Devices, Inc PDIP-8



OP462GSZ

Analog Devices, Inc SOIC-14



OP467GPZ

Analog Devices, Inc PDIP-14



OP42AZ

Analog Devices, Inc CDIP-8



OP37GS

Analog Devices, Inc SOIC-8



**OP2177ARM** 

Analog Devices, Inc MSOP8



OP400GPZ

Analog Devices, Inc PDIP-14