

## ADM3222ARUZ

Data Sheet

High-Speed, +3.3V, 2-Channel RS232/V.28 Interface Device with 460kBPS Data Rate and	
Shutdown and Enable Pins	

Manufacturers	Analog Devices, Inc
Package/Case	TSSOP-20
Product Type	Interface ICs
RoHS	Pb-free Halide free



Images are for reference only

Please submit RFQ for ADM3222ARUZ or <u>Email to us: sales@ovaga.com</u> We will contact you in 12 hours.

<u>RFQ</u>

## **General Description**

Lifecycle

The ADM3202/ADM3222/ADM1385 conform to the EIA-232E and CCITT V.28 specifications and operate at data rates up to 230 kbps. Four external 0.1  $\mu$ F charge pump capacitors are used for the voltage doubler/inverter permitting operation from a single +3.3 V supply.

The ADM3222/ADM1385 contain additional enable and shutdown circuitry. The EN input may be used to three-state the receiver outputs. The SD input is used to power down the charge pump and transmitter outputs reducing the quiescent current to less than 1  $\mu$ A. The receivers remain enabled during shutdown unless disabled using EN.

The ADM3202 is available in a 16-lead DIP, narrow and wide SO as well as a space saving TSSOP package. The ADM3222 is available in 18 lead DIP, SO and in 20 lead SSOP and TSSOP. The ADM1385 is available in a 20 lead SSOP package and is pin compatible with the LTC1385 CG.

## Features

460 kbps Data Rate

Specified at 3.3 V

Meets EIA-232E Specifications

0.1 µF Charge Pump Capacitors

Low Power Shutdown (ADM3222E and ADM1385)

Upgrade for MAX3222/32 and LTC1385

DIP, SO, SOIC, SSOP and TSSOP Package Options

ESD Protection to IEC1000-4-2 (801.2) on RS-232 Pins (ADM3202 Only)±8 kV: Contact Discharge±15 kV: Air-Gap Discharge





## **Related Products**



ADV7181CBSTZ Analog Devices, Inc LQFP-64



AD724JR Analog Devices, Inc SOIC-16







ADV7341BSTZ Analog Devices, Inc LQFP-64





Analog Devices, Inc SOP8

AD8170AR

ADV7393BCPZ

Analog Devices, Inc LFCSP-VQ-40

ADV7390BCPZ

Analog Devices, Inc QFN32



QFN32

ADUM4160BRIZ

Analog Devices, Inc SOIC-16