



Data Sheet

Analog to Digital Converters - ADC Data Acquisition System IC 12-Bit

Manufacturers Analog Devices, Inc.

Package/Case SOIC-28

Product Type Data Conversion ICs

RoHS Rohs

Lifecycle



Images are for reference only

Please submit RFQ for AD7874BRZ or Email to us: sales@ovaga.com We will contact you in 12 hours.

RFO

General Description

The aperture delay of the four track/hold amplifiers is small and specified with minimum and maximum limits. This allows several AD7874s to sample multiple input channels simultaneously without incurring phase errors between signals connected to several devices. A reference output/reference input facility also allows several AD7874s to be driven from the same reference source.

In addition to the traditional dc accuracy specifications such as linearity, full-scale and offset errors, the AD7874 is also fully specified for dynamic performance parameters including distortion and signal-to-noise ratio.

The AD7874 is fabricated in Analog Devices' Linear Compatible CMOWS (LC2MOS) process, a mixed technology process that combines precision bipolar circuits with low-power CMOS logic. The part is available in a 28-pin, 0.6" wide, plastic or hermetic dual-in-line package (DIP), in a 28-terminal leadless ceramic chip carrier (LCCC) and in a 28-pin SOIC.

Features Application

Four On-Chip Track/Hold Amplifiers Sonar

Simultaneous Sampling of 4 Channels Motor Controllers

Fast 12-Bit ADC with 8 µs Conversion Time/Channel Adaptive Filters

29 kHz Sample Rate for All Four Channels Digital Signal Processing

On-Chip Reference



Related Products



ADAS3022BCPZ
Analog Devices, Inc
LFCSP-40



AD574AJNZ
Analog Devices, Inc
PDIP-28



Analog Devices, Inc TQPF-32



AD7401YRWZ
Analog Devices, Inc
SOIC-16



AD7938BSUZ
Analog Devices, Inc
TQFP-32



Analog Devices, Inc TSSOP-24

AD7192BRUZ-REEL



AD7124-8BCPZ-RL7
Analog Devices, Inc
LFCSP-32



AD9680BCPZ-500
Analog Devices, Inc
LFCSP-64