


Driver 1.5A 2-OUT Low Side Non-Inv 8-Pin PDIP Tube

Manufacturers	Microchip Technology, Inc
Package/Case	PDIP-8
Product Type	Power Management ICs
RoHS	
Lifecycle	



Images are for reference only

Please submit RFQ for TC427CPA or [Email to us: sales@ovaga.com](mailto:sales@ovaga.com) We will contact you in 12 hours.

[RFQ](#)

General Description

The TC426/TC427/TC428 are dual CMOS high-speed drivers. A TTL/CMOS input voltage level is translated into a rail-to-rail output voltage level swing. The CMOS output is within 25mV of ground or positive supply. The low impedance, high-current driver outputs swing a 1000pF load 18V in 30nsec. The unique current and voltage drive qualities make the TC426/TC427/TC428 ideal power MOSFET drivers, line drivers, and DC-to-DC converter building blocks. Input logic signals may equal the power supply voltage. Input current is a low 1A, making direct interface to CMOS/bipolar switch-mode power supply control ICs possible, as well as open-collector analog comparators. Quiescent power supply current is 8mA maximum. The TC426 requires 1/5 the current of the pin-compatible bipolar DS0026 device. This is important in DC-to-DC converter applications with power efficiency constraints and high-frequency switch-mode power supply applications. Quiescent current is typically 6mA when driving a 1000pF load 18V at 100kHz. The inverting TC426 driver is pin-compatible with the bipolar DS0026 and MMH0026 devices. The TC427 is noninverting; the TC428 contains an inverting and non-inverting driver. Other pin compatible driver families are the TC1426/27/28, TC4426/27/28, and TC4426A/27A/28A.

For product comparison, please consider:TC4427A

Features

High-Speed

High Peak Output Current: 1.5A

High Output Voltage Swing: VDD – 25mV GND +25mV

Low Input Current(Logic '0' or '1'): 1mA

TTL/CMOS Input Compatible

Available in Inverting and Noninverting Configurations

Wide Operating Supply Voltage: 4.5V to 18V

Current Consumption:

Inputs Low: 0.4mA

Inputs High: 8mA

Single Supply Operation

Low Output Impedance: 6Ω

Pinout Equivalent of DS0026 and MMH0026

Latch-Up Resistant: Withstands > 500mA Reverse Current

Related Products




[TC7662BEOA](#)

Microchip Technology, Inc
SOIC-8




[TC4420EOA](#)

Microchip Technology, Inc
SOIC-8



[TC4428EOA](#)

Microchip Technology, Inc
SOIC-8



[TC4426AEOA](#)

Microchip Technology, Inc
SOIC-8



[TC4426EPA](#)

Microchip Technology, Inc
PDIP-8



[TC7107ACKW](#)

Microchip Technology, Inc
MQFP-44



[TC1015-1.8VCT713](#)

Microchip Technology, Inc
SOT-23-5



[TC7662BCOA713](#)

Microchip Technology, Inc
SOIC-8