



Data Sheet

Precision Micropower, Low Dropout Voltage References

Manufacturers Analog Devices, Inc

Package/Case SOP-8

Product Type Power Management ICs

RoHS Pb-free Halide free

Lifecycle



Images are for reference only

Please submit RFQ for REF193GSZ or Email to us: sales@ovaga.com We will contact you in 12 hours.

RFO

General Description

The REF19x series is made up of micropower, low dropout voltage (LDV) devices, providing stable output voltage from supplies as low as 100 mV above the output voltage and consuming less than 45 μ A of supply current. In sleep mode, which is enabled by applying a low TTL or CMOS level to the SLEEP pin, the output is turned off and supply current is further reduced to less than 15 μ A.

The REF19x series references are specified over the extended industrial temperature range (-40° C to $+85^{\circ}$ C) with typical performance specifications over -40° C to $+125^{\circ}$ C for applications, such as automotive.

All electrical grades are available in an 8-lead SOIC package; the PDIP and TSSOP packages are available only in the lowest electrical grade.

Features

Initial Accuracy: ±2 mV Max

Temperature Coefficient: 5 ppm/°C Max

Low Supply Current: 45 µA Max

Sleep Mode: 15 µA Max

Low Dropout Voltage

Load Regulation: 6 ppm/mA

Line Regulation: 4 ppm/V

High Output Current: 30 mA

Short-Circuit Protection

Application

Portable instruments

ADCs and DACs

Smart sensors

Solar powered applications

Loop-current-powered instruments

Related Products



REF02CPZ

Analog Devices, Inc DIP8



REF192GRUZ

Analog Devices, Inc TSSOP-8



ADP5071AREZ

Analog Devices, Inc TSSOP-20



REF198ESZ

Analog Devices, Inc SOIC-8



ADP3336ARMZ-REEL7

Analog Devices, Inc MSOP-8



REF192FSZ

Analog Devices, Inc SOIC-8



ADM811TARTZ-REEL7

Analog Devices, Inc SOT23



AD1580BRTZ-REEL7

Analog Devices, Inc

SOT-23