


20V, 500mA, Ultralow Noise, Ultrahigh PSRR Linear Regulator

Manufacturers	<a href="#">Analog Devices, Inc</a>
Package/Case	12-Lead MSOP w/ EP
Product Type	Power Management ICs
RoHS	
Lifecycle	



Images are for reference only

Please submit RFQ for LT3045HMSE#PBF or [Email to us: sales@ovaga.com](mailto:sales@ovaga.com) We will contact you in 12 hours.

[RFQ](#)

## General Description

The LT3045 is a high performance low dropout linear regulator featuring LTC's ultralow noise and ultrahigh PSRR architecture for powering noise sensitive applications. Designed as a precision current reference followed by a high performance voltage buffer, the LT3045 can be easily paralleled to further reduce noise, increase output current and spread heat on the PCB.

The device supplies 500mA at a typical 260mV dropout voltage. Operating quiescent current is nominally 2.2mA and drops to  $<<1\mu\text{A}$  in shutdown. The LT3045's wide output voltage range (0V to 15V) while maintaining unity-gain operation provides virtually constant output noise, PSRR, bandwidth and load regulation, independent of the programmed output voltage. Additionally, the regulator features programmable current limit, fast start-up capability and programmable power good to indicate output voltage regulation.

The LT3045 is stable with a minimum  $10\mu\text{F}$  ceramic output capacitor. Built-in protection includes reverse-battery protection, reverse-current protection, internal current limit with foldback and thermal limit with hysteresis. The LT3045 is available in thermally enhanced 12-Lead MSOP and 10-Lead  $3\text{mm} \times 3\text{mm}$  DFN packages.

VIOC FunctionLT3045-1YesLT3045No

## Features

Ultralow RMS Noise:  $0.8\mu\text{VRMS}$  (10Hz to 100kHz)

Ultralow Spot Noise:  $2\text{nV}/\sqrt{\text{Hz}}$  at 10kHz

Ultrahigh PSRR: 76dB at 1MHz

Output Current: 500mA

Wide Input Voltage Range: 1.8V to 20V

Single Capacitor Improves Noise and PSRR

100 $\mu\text{A}$  SET Pin Current:  $\pm 1\%$  Initial Accuracy

Single Resistor Programs Output Voltage

High Bandwidth: 1MHz

Programmable Current Limit

Low Dropout Voltage: 260mV

Output Voltage Range: 0V to 15V

Programmable Power Good

Fast Start-Up Capability

Precision Enable/UVLO

Parallelable for Lower Noise and Higher Current

Internal Current Limit with Foldback

Minimum Output Capacitor: 10 $\mu\text{F}$  Ceramic

Reverse-Battery and Reverse-Current Protection

12-Lead MSOP and 10-Lead 3mm  $\times$  3mm DFN Packages

## Application

RF Power Supplies: PLLs, VCOs, Mixers, LNAs, PAs

Very Low Noise Instrumentation

High Speed/High Precision Data Converters

Medical Applications: Imaging, Diagnostics

Precision Power Supplies

## Related Products



### [LT3763EFE](#)

Analog Devices, Inc  
TSSOP28



### [LT1038CK](#)

Analog Devices, Inc  
TO-3



### [LTC4417IUF](#)

Analog Devices, Inc  
QFN-24



### [LTC3440EMS](#)

Analog Devices, Inc  
MSOP10



[LTC1966CMS8#PBF](#)

Analog Devices, Inc  
MSOP-8P



[LTM8045EY#PBF](#)

Analog Devices, Inc  
BGA40



[LTC2990IMS#PBF](#)

Analog Devices, Inc  
10MSOP



[LT4295IUFD#PBF](#)

Analog Devices, Inc  
28-WFQFN