

Voltage Reference, Ultralow Noise, High Accuracy, Series - Fixed, ADR4550 Series, 5V, NSOIC-8

Manufacturers	Analog Devices, Inc
Package/Case	SOIC-8
Product Type	Power Management ICs
RoHS	Rohs
Lifecycle	



Images are for reference only

Please submit RFQ for ADR4550BRZ or [Email to us: sales@ovaga.com](mailto:sales@ovaga.com) We will contact you in 12 hours.

[RFQ](#)

General Description

The ADR4520/ADR4525/ADR4530/ADR4533/ADR4540/ADR4550 devices are high precision, low power, low noise voltage references featuring $\pm 0.02\%$ B, C, and D grade maximum initial error, excellent temperature stability, and low output noise.

This family of voltage references uses an innovative core topology to achieve high accuracy while offering industry-leading temperature stability and noise performance. The low, thermally induced output voltage hysteresis and low long-term output voltage drift of the devices also improve system accuracy overtime and temperature variations.

A maximum operating current of 950 μA and a maximum low dropout voltage of 300 mV allow the devices to function very well in portable equipment.

The ADR4520/ADR4525/ADR4530/ADR4533/ADR4540/ADR4550 series of references are each provided in an 8-lead SOIC and are available in a wide range of output voltages, all of which are specified over the extended industrial temperature range of -40°C to $+125^{\circ}\text{C}$.

APPLICATIONS

Features

Maximum temperature coefficient (TCV

OUT

0.8 ppm/ $^{\circ}\text{C}$ (D grade 0°C to 70°C)

1 ppm/ $^{\circ}\text{C}$ (C grade 0°C to 70°C)

2 ppm/ $^{\circ}\text{C}$ (B grade -40°C to $+125^{\circ}\text{C}$)

4 ppm/ $^{\circ}\text{C}$ (A grade -40°C to $+125^{\circ}\text{C}$)

Application

Precision data acquisition systems

High resolution data converters

High precision measurement devices

Industrial instrumentation

Medical devices

Automotive battery monitoring

Output noise (0.1 Hz to 10 Hz):

1 μV p-p at V

OUT

Initial output voltage error:

B, C, D grade: $\pm 0.02\%$ (maximum)

Input voltage range: 3 V to 15 V

0.8 ppm/ $^{\circ}\text{C}$ (D grade 0°C to 70°C)

1 ppm/ $^{\circ}\text{C}$ (C grade 0°C to 70°C)

2 ppm/ $^{\circ}\text{C}$ (B grade -40°C to $+125^{\circ}\text{C}$)

4 ppm/ $^{\circ}\text{C}$ (A grade -40°C to $+125^{\circ}\text{C}$)

B, C, D grade: $\pm 0.02\%$ (maximum)

Operating temperature:

A grade and B grade: -40°C to $+125^{\circ}\text{C}$

C grade: 0°C to $+70^{\circ}\text{C}$

Output current: +10 mA source/ -10 mA sink

Low quiescent current: 950 μA (maximum)

Low dropout voltage: 300 mV at 2 mA (V

OUT

8-lead SOIC package and LCC package

AEC-Q100 qualified for automotive applications

Long-term drift: 8 ppm typical at 4500 hours

A grade and B grade: -40°C to $+125^{\circ}\text{C}$

C grade: 0°C to $+70^{\circ}\text{C}$

Related Products



[ADP3336ARMZ-REEL7](#)

Analog Devices, Inc
MSOP-8




[AD737JRZ](#)

Analog Devices, Inc
SOP-8



[ADP3367ARZ](#)

Analog Devices, Inc
SOIC-8



[AD636JH](#)

Analog Devices, Inc
TO-100-10




[ADP3330ARTZ3.3-RL7](#)

Analog Devices, Inc
SOT-23-6



[ADR434BRZ](#)

Analog Devices, Inc
SOIC-8



[ADR421ARZ](#)

Analog Devices, Inc
SOP-8



[ADR3412ARJZ-R7](#)

Analog Devices, Inc
SOT-23-6