

# NLSV8T244MUTAG

Data Sheet

#### 8 Bit Unidirectional Translator, Translation - Voltage Levels SBN 8-BIT TRANSLATOR

Manufacturers	ON Semiconductor, LLC	
Package/Case	20-UFDFN	HARRAN CONTRACTOR
Product Type	Logic ICs	C. R.
RoHS	Rohs	
Lifecycle		Images are for reference only
Please submit RFQ for NLSV8T244MUTAG or <u>Email to us: sales@ovaga.com</u> We will contact you in 12 hours.		

### **General Description**

The NLSV8T244 is a 8 bit configurable dual supply voltage level translator. The input An and output Bn ports are designed to track two different power supply rails, VCCA and VCCB respectively. Both supply rails are configurable from 0.9 V to 4.5 V allowing universal low voltage translation from the input An to the output Bn port.

#### Features

VCCA and VCCB can be 0.9 V to 4.5 V

Wide Operating Voltage Range

HighSpeed w/ Balanced Propagation Delay

Inputs and Outputs have OVT Protection to 4.5 V

Nonpreferential VCCA and VCCB Sequencing

Outputs at 3State until Active VCC is Reached

PowerOff Protection

Outputs Switch to 3State with VCCB at GND

UltraSmall Packaging: 4.0 mm x 2.0 mm UDFN20

Dolotod Droduots

## Application

ONSEMI



#### **NLSV2T244MUTAG**

ON Semiconductor, LLC UDFN8



## NL27WZU04DFT2G ON Semiconductor, LLC

SC-70-6



## NL17SZ126DFT2G ON Semiconductor, LLC

SC-70-5



## NL27WZ00USG ON Semiconductor, LLC

VFSOP-8











### NLSV1T34DFT2G

ON Semiconductor, LLC SC-88A

#### NL17SZ32DFT2G

ON Semiconductor, LLC SC-70

#### NL17SZ00DFT2G

ON Semiconductor, LLC SC-70

## NL37WZ17USG

ON Semiconductor, LLC US8-8