🔉 ovaga

24LC02BT-I/SN

Data Sheet

Single/Dual/Triple/Quad ATM/Packet PHYs with Built-In LIU, EEPROM 256x8 - 1.8V

Manufacturers	Microchip Technology, Inc
Package/Case	SOIC-8
Product Type	Memory
RoHS	
Lifecycle	



Images are for reference only

Please submit RFQ for 24LC02BT-I/SN or Email to us: sales@ovaga.com We will contact you in 12 hours.

<u>RFQ</u>

General Description

The Microchip Technology Inc. 24AA02/24LC02B is a 2Kb I2CTM compatible Serial EEPROM. The device is organized as one block of 256 x 8-bit memory with a 2-wire serial interface. Low-voltage design permits operation down to 1.7V, with standby and active currents of only 1 μ A and 1 mA, respectively. The 24XX02 also has a page write capability for up to 8 bytes of data. The 24XX02 is available in the standard 8-pin PDIP, surface mount SOIC, TSSOP, 2x3 DFN and MSOP packages and is also available in the 5-lead SOT-23 package.

Features

Single supply with operation down to 2.5V for 24LC02B devices

Low-power CMOS technology

2-wire serial interface, I2CTM compatible

Schmitt Trigger inputs for noise suppression

Output slope control to eliminate ground bounce

100 kHz and 400 kHz clock compatibility

Page write time 3 ms, typical

More than 1 million erase/write cycles

Data retention >200 years





Related Products



AT24CM02-SSHM-B Microchip Technology, Inc

SOIC-8

24FC512-I/SM

Microchip Technology, Inc SOIJ-8





AT24CM02-SSHD-B

Microchip Technology, Inc SOIC-8

24AA512-I/SM

Microchip Technology, Inc SOIJ-8



AT24C512C-SSHM-T

Microchip Technology, Inc SOIC-8



24LC256-I/ST

Microchip Technology, Inc TSSOP-8



24LC32AT-I/SN

Microchip Technology, Inc SOIC-8



AT24C04D-MAHM-T

Microchip Technology, Inc UDFN-8