

QS3VH253QG8

Data Sheet

Bus Switch, 2 Channels, Bus Switch, 9 ohm, QSOP, 16 Pins New

Manufacturers	Renesas Technology Corp	
Package/Case	TSOP20	
Product Type	Logic ICs	WHARMAR BURNER
RoHS	Rohs	Suc.
Lifecycle		Images are for reference only
Please submit RFO f	or QS3VH253QG8 or <u>Email to us: sales@ovaga.com</u> We wil	l contact you in 12 hours. RFO

General Description

The QS3VH253 HotSwitch Dual 4:1 multiplexer/demultiplexer is a high bandwidth bus switch with very low ON resistance, resulting in under 250ps propagation delay through the switch. The combination of near-zero propagation delay, high OFF impedance, and over-voltage tolerance makes the QS3VH253 ideal for high performance communication applications. The QS3VH253 operates from -40C to +85C.

Features

N channel FET switches with no parasitic diode to VCC

Isolation under power-off conditions

No DC path to VCC or GND

5V tolerant in OFF and ON state

5V tolerant I/Os

Low RON - 4 ohm typical

Flat RON characteristics over operating range

Rail-to-rail switching 0 - 5V

Bidirectional dataflow with near-zero delay: no added ground bounce

Excellent RON matching between channels

VCC operation: 2.3V to 3.6V

High bandwidth - up to 500MHz

LVTTL-compatible control Inputs

Undershoot Clamp Diodes on all switch and control Inputs

Low I/O capacitance, 4pF typical

Available in 16 pin QSOP and TSSOP packages

Related Products



OS3861PAG8

Renesas Technology Corp TSSOP-24



QS3257QG Renesas Technology Corp QSOP-16



QS3VH125QG Renesas Technology Corp



OS3384OG

Renesas Technology Corp QSOP-24

QS3125QG

Renesas Technology Corp QSOP-16

QS3861QG

Renesas Technology Corp QSOP-24



Ovaga Technologies Limited



QS3861PAG

Renesas Technology Corp

TSSOP-24



<u>QS3245QG</u>

Renesas Technology Corp QSOP-20